

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 October 2004 (21.10.2004)

PCT

(10) International Publication Number
WO 2004/089508 A1

(51) International Patent Classification⁷: **B01D 39/00**

Seo-gu, Daejeon 302-781 (KR). MIN, Wha-Sik [KR/KR];
101-602 Expo Apt., Jeonmin-dong, Yusong-gu, Daejeon
305-761 (KR).

(21) International Application Number:
PCT/KR2004/000856

(22) International Filing Date: 14 April 2004 (14.04.2004)

(74) Agent: C & S PATENT AND LAW OFFICE; C-2306
Daelim Acrotel, 467-6 Dogok-dong Kangnam-gu, Seoul
135-971 (KR).

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2003-0023515 14 April 2003 (14.04.2003) KR
10-2004-0012642 25 February 2004 (25.02.2004) KR

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): SK COR-
PORATION [KR/KR]; 99 Seorin-dong Jongro-ku, Seoul
110-110 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KIM, Young-Woo
[KR/KR]; 109-204 Chunggoo Apt., Jeonmin-dong,
Yusong-gu, Daejeon 305-390 (KR). MIN, Joon-Seok
[KR/KR]; 106-404 Expo Apt., 464-1 Jeonmin-dong
Yusong-gu, Daejeon 305-761 (KR). KIM, Sung-Hyoan
[KR/KR]; 102-905 Sejong Apt., Jeonmin-dong, Yu-
song-gu, Daejeon 305-728 (KR). LEE, Chang-Q
[KR/KR]; 104-1108 Sangroksoo Apt., Mannyun-dong,


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: CATALYTIC FILTER FOR REMOVING SOOT PARTICULATES FROM DIESEL ENGINE EXHAUST AND METHOD OF PREPARING THE SAME



(57) Abstract: Disclosed is a catalytic filter for removing soot particu-
lates from diesel engine exhaust, which is comprised of monolithic ox-
idation catalyst upstream of the catalytic filter, which effectively ox-
idize gaseous pollutants and volatile organic fractions, and a catalyzed
wall-flow filter downstream serving to low temperature combustion of
soot particulates collected on the filter. Also, the preparation method of
the catalytic filter is provided, including the colloidal mixture solution
of platinum group metal salts and other metal salts with a water-soluble
polymer and a reducing agent, which is then impregnated on a catalyst
support, followed by calcining at high temperatures. In the present in-
vention, use of the catalytic filter provides effective means of abating
diesel exhaust pollutant emissions, that is, particulate matter (PM) and
gaseous pollutants (HC, CO, NO_x).

BEST AVAILABLE COPY

WG 2004/089508 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

CATALYTIC FILTER FOR REMOVING SOOT PARTICULATES FROM DIESEL
ENGINE EXHAUST AND METHOD OF PREPARING THE SAME

Technical Field

The present invention relates to catalytic wall-flow
5 filters for removal of soot particulates from diesel engine
exhaust, and preparation methods thereof. More specifically,
the present invention relates to a catalytic filter system,
capable of continuously burning soot trapped on the filter,
thereby regenerating the filter while reducing harmful exhaust
10 gases of carbon monoxide (CO), nitrogen oxides (NO_x) and
unburned hydrocarbons (HC) therein, as well, and a method of
preparing the catalytic filter.

Background Art

Generally, particulate matters in diesel engine exhaust
15 are composed of carbonaceous soot particulates with average
diameter of 0.3 μm , comprising soots, sulfates and heavy
hydrocarbons, which are derived from lubricating oil and
unburned fuel. Especially, soot particulates, caused by
incomplete combustion of diesel fuel, increase visual discomfort
20 and the degree of air pollution that causes offensive odors, and
as well, can damage human health. Therefore, emission control
standards for soot particulates in diesel engine exhaust have
been further strengthened, but practically applicable

technologies satisfying the current emission control standards have not been presently commercially developed. Thus, it is urgently required to develop novel technologies for abatement of the generation of soot particulates and after-treatment of the soot particulates. At present, there are proposed methods of reducing emissions of soot particulates by improvement of engine control technologies or by use of a fuel additive, and methods of removing soot particulates from exhaust gas through a post-treatment device, such as a diesel particulate filter.

As for the method of reducing emissions of the soot particulates, desirable results cannot be obtained by the improvement of engine technology alone for some vehicles. Meanwhile, the use of fuel additives is not cost-effective and may cause secondary pollution by emission thereof into the atmosphere.

The method using post-treatment device includes a trapping process of soot particulates in the exhaust gas by use of a filter medium, and a combustion process of the trapped soot particulates to regenerate inherent filtering performance of the filter medium. However, use of the post-treatment device suffers from excessive increase of back-pressure due to the accumulation of the trapped soots when the trapped soots are not continuously regenerated, resulting in worsening engine performance.

Hence, a number of different options for controlling particulates are diversely attempted, and are largely classified into active regeneration and passive catalytic regeneration.

The active regeneration is used to forcibly combust the soot particulates to regenerate the filter by use of a burner or an electric heater, which is advantageous in terms of superior regeneration performance. However, the above process is
5 disadvantageous in that excessive thermal shock applied to the filter medium leads to the damage of filter medium, while negating economic benefits due to the use of complicated control units.

Additionally, the regeneration process of the filter
10 medium by adding an organic metal additive to diesel fuel is disadvantageous in that the added metal component is deposited in the engine, and fine metallic additive particles not trapped in the filter medium is discharged to the atmosphere, thus causing secondary pollution.

15 Regarding the passive catalytic regeneration, U.S. Patent No. 4,902,487 (corresponding to Japanese Patent No. 3,012,249) discloses a catalytic, two-stage, passive particulate filter system including a monolithic oxidation catalyst (upstream) and a ceramic wall-flow diesel filter (downstream). The monolithic
20 oxidation catalyst allows to convert a portion of nitrogen monoxide (NO) contained in diesel exhaust gases into nitrogen dioxide (NO₂), which is a much stronger oxidizing agent than oxygen. As such, NO₂ has a concentration range of 100-2,000 ppm, and reacts with the soot particulates trapped on the particulate
25 filter downstream, and thus, allows the sooty particulates to be combusted at 225-300°C, thereby purifying the diesel engine exhaust gases. However, since the oxidation catalyst upstream

acts also to facilitate generation of sulfate by oxidation of sulfur dioxide (SO₂) in the exhaust gas, the use of ultra low sulfur diesel (ULSD) fuel is required. In addition, NO₂ formation rate rapidly decreases at higher temperatures due to the constraint of thermodynamic equilibrium. Therefore, it is required to develop a catalytic particulate filter that has a sufficiently low balance point temperature (BPT) to continuously remove soot particulates at the typical exhaust temperature range.

Disclosure of the Invention

Leading to the present invention, the intensive and thorough research on catalytic filters for removal of soot particulates from diesel engine exhaust, carried out by the present inventors aiming to avoid the problems encountered in the related art, resulted in that a colloidal solution of a platinum group metal (PGM) salt and a metal salt impregnated on a catalyst support is used, instead of conventional aqueous metal salt solutions, thus obtaining a monolithic oxidation catalyst upstream of the catalytic filter, which effectively oxidize volatile organic fractions, and a catalyzed wall-flow filter downstream thereof serving to low temperature combustion of soot particulates collected on the filter, thereby removing soot particulates in exhaust gas.

Accordingly, an object of the present invention is to provide a catalyzed filter for use in decreasing balance point

temperatures (BPT) and continuously removing soot particulates in diesel engine exhaust gases, and a method of preparing the same.

Another object of the present invention is to provide a catalyzed filter for reducing gaseous pollutants such as carbon monoxide ("CO"), unburned hydrocarbons ("HC"), and nitrogen oxides ("NO_x") in diesel engine exhaust, and a method of preparing the same.

To accomplish the above objects, the present invention provides a method of preparing an oxidation catalyst for oxidizing volatile organic fraction and a catalyzed wall-flow filter for use in removing soot particulates from diesel engine exhaust, including preparing a PGM salt and a transition/alkali metal salt with a water-soluble polymer compound and a reducing agent, to obtain a first colloidal solution, which is then washcoated to a catalyst-support-coated monolithic ceramic substrate, followed by calcination process at high temperatures, to obtain an oxidation catalyst; and treating a PGM salt and a metal salt mixture including at least one selected from a first group of catalyst metal to increase oxidation activity for nitrogen monoxide (NO) and at least one selected from a second group of catalyst metal to decrease a combustion temperature of soot particulates by oxidizing agents, such as nitrogen dioxide and oxygen, with a water-soluble polymer compound and a reducing agent, to obtain a second colloidal solution, which is then washcoated on a catalyst-support-coated wall-flow filter, followed by calcination process at high temperatures, to obtain

a catalyzed wall-flow filter.

In such cases, the metal salt mixture for a catalyzed wall-flow filter additionally includes at least one selected from a third group of catalyst metal to prevent oxidation of sulfur
5 dioxide.

Brief Description of the Drawings

The above and other objects, features and other advantages of the present invention will be more clearly understood from
10 the following detailed description taken in conjunction with the accompanying drawings, in which:

FIGS. 1a to 1d are graphs showing a reduction of soot particulates (PM), nitrogen oxides (NO_x), carbon monoxide (CO) and unburned hydrocarbons (THC) in diesel engine exhaust after
15 mounting the catalytic filter of the present invention, comparing with the case without the catalytic filter of the present invention.

FIG. 2 is a graph representing balance point temperature (BPT) of the catalytic filter of the present invention.

20 FIG. 3 is a graph showing the change of the pressure difference of the catalytic filter of the present invention per day.

Best Mode for Carrying Out the Invention

25 Hereinafter, a detailed description will be given of the

present invention with reference to the appended drawings.

Based on the present invention, a catalytic filter for removing soot particulates from diesel engine exhaust is provided, comprised of monolithic oxidation catalyst upstream of the catalytic filter, which effectively oxidize gaseous pollutants and volatile organic fractions and a catalyzed wall-flow filter downstream serving to low temperature combustion of soot particulates collected on the filter. In addition, a preparation method of such a catalytic filter is provided.

10 The catalytic filter of the present invention can function to continuously regenerate the soot particulates collected on the filter during diesel engine operation and the purified gas is then discharged to the atmosphere.

Such a catalytic filter, for use in removing the soot particulates from the diesel engine exhaust, is prepared by treating a platinum group metal (PGM) salt and a transition/alkali metal salt with a water-soluble polymer compound and a reducing agent, to obtain a first colloidal solution, which is then washcoated to a catalyst-support-coated monolithic ceramic substrate, and followed by calcination process at high temperatures to form an oxidation catalyst; and treating a PGM salt and a metal salt mixture including at least one selected from a first group of catalyst metal to increase oxidation activity for nitrogen monoxide (NO) and at least one selected from a second group of catalyst metal to decrease a combustion temperature of soot particulates by nitrogen dioxide (NO₂) and oxygen (O₂) with a water-soluble polymer compound and a

reducing agent, to obtain a second colloidal solution, which is then washcoated on a catalyst-support-coated wall-flow filter, followed by calcination process at high temperatures, to form a catalyzed wall-flow filter.

Specifically, a conventional support or heat-resistant filter medium, for example, flow-through ceramic monolith, is supported with a catalyst material having high oxidation activity to oxidize gaseous emissions and soluble organic fraction in the exhaust gas.

Moreover, the catalyst mounted upstream reacts with the diesel engine exhaust to induce favorable condition for burning the soot particles collected on the filter downstream. As such, the catalyst mounted upstream is referred to as 'oxidation catalyst'.

As for the oxidation catalyst, a catalyst composition is formulated to maintain high oxidation activity for carbon monoxide (CO) and unburned hydrocarbons (HC) in the diesel engine exhaust, and to oppress the oxidation of sulfur dioxide (SO₂) in the exhaust stream, resulting in inducing an atmosphere favorable to combustion of the soot particulates collected on the wall-flow filter downstream.

Concerning the substrate of the oxidation catalyst,—the flow-through substrate is washcoated with the high surface area oxide support to uniformly disperse the active metal components, and then supported with the colloidal solution of the PGM salt and the transition/alkali metal salt.

The high surface area oxide support is exemplified by

alumina, silica, and/or titania, which preferably contains 0.1-1.5 g/in³ of TiO₂ and 0.1-1.5 g/in³ of SiO₂, with a weight ratio of TiO₂ to SiO₂ of 2-4:1, to have an optimal catalyst support properties. If the weight ratio of TiO₂ to SiO₂ is less than
5 2:1, the surface area for uniformly supporting the catalyst material becomes small. Meanwhile, if the weight ratio exceeds 4:1, coatability of the suspension solution to the filter drastically decreases.

The PGM salt includes Pt, Pd, Ru, Ir, Rh, or combinations
10 thereof, and the transition/alkali metal salts have Ba, Ce, Co, Cr, Cs, Cu, Fe, K, Mg, Mn, Mo, Ni, Pb, V, W, or combinations thereof. As such, the weight ratio of the PGM to the transition/alkali metal is preferably in the range of 1:0.1-5. When the weight ratio is less than 1:0.1, sulfate is generated
15 in a large amount by the oxidation of sulfur dioxide in the exhaust gas. Whereas, when the weight ratio exceeds 1:5, the oxidation activity for gaseous and volatile pollutants decreases.

The platinum group metal is used in the amount of 5-45
20 g/ft³. The amount less than 5 g/ft³ results in low oxidation activity for gaseous pollutants (CO, HC, and NO) whereas the amount exceeding 45 g/ft³ leads to excessive use of expensive precious metal, thus negating economic benefits.

Examples of a starting material of palladium (Pd) include
25 palladium nitrate, palladium chloride, tetraminepalladium dichloride, etc. Also, examples of a starting material of platinum (Pt) include chloroplatinic acid,

diaminedinitritoplatinum, diaminetetrachloroplatinum, etc. A starting material of rhodium (Rh) is exemplified by rhodium chloride, rhodium nitrate, triamminerhodium hexachloride, etc.

The colloidal solution for the oxidation catalyst is prepared from treatment of the PGM salt and the transition/alkali metal salt with a water-soluble polymer compound and a reducing agent by colloidal reduction method. Conventionally, a PGM salt is supported to a high-surface area oxide support and then calcined for activation thereof. At this time, however, nano-size precious metal particles are agglomerated upon reduction to a precious metal, thus worsening metal dispersion. Whereas, in the present invention, the precious metal salt in the state of protective copolymer colloidal solution is reduced to precious metal, which is then supported to a high-surface area oxide support and calcined, thereby solving the above problems.

The water-soluble protective copolymer compound is exemplified by polyvinylalcohol, polyvinylpyrrolidone, polymethylacrylate, etc. Examples of the reducing agent include methanol, ethanol, hydrazine, or a mixture of methanol/sodium hydroxide.

The thus obtained colloidal solution is properly controlled in concentration by use of water or alcohol as a diluent.

The above mentioned catalyst is then calcined at high temperatures, for example, 500-600°C, to obtain the oxidation catalyst.

Further, catalyst materials are supported to the filter medium downstream to decrease the combustion temperature of the collected soot particulates. Like this, the catalyst mounted downstream is referred to as 'catalyzed wall-flow filter'.

5 The soot particulates collected on the catalyzed wall-flow filter are converted to harmless gases by the catalytic combustion reaction with oxygen in the exhaust gas and NO₂, which is produced from oxidation of NO through flowing the catalyzed-wall, and then, discharged to the atmosphere.

10 As in the preparation of the oxidation catalyst, the catalyst composition of the catalyzed wall-flow filter is obtained by supporting the second colloidal solution of the PGM salt and the metal salt mixture to the catalyst- support-coated wall-flow filter.

15 As such, the PGM salt used for the catalyzed wall-flow filter equals to that used for the preparation of the oxidation catalyst.

 The metal salt mixture includes at least one selected from the first group of catalyst metal to increase the catalytic
20 combustion activity for the collected soot particulates, and at least one selected from the second group of catalyst metal to lower the combustion temperature of the soot particulates.

 Preferably, the first group of catalyst metal is selected from Ba, Cr, Mn, Fe, Co, Ni, Cu, Mo, V and Pb, and the second
25 group of catalyst metal is selected from Li, Na, K, Mg, Ca and Cs. In such cases, the catalyzed filter contains 5-45 g/ft³ of the PGM, 10-120 g/ft³ of the first group of catalyst metal, and

5-40 g/ft³ of the second group of catalyst metal.

The above metal salt mixture further includes at least one selected from a third group of catalyst metal to prevent oxidation of sulfur dioxide.

5 The third group of catalyst metal is selected from among V, W and Mo, and is used in the amount of 10-150 g/ft³.

Hence, the second colloidal solution of the catalyzed wall-flow filter is prepared by treating the PGM salt and the metal salt mixture with the water-soluble polymer compound and
10 the reducing agent in colloidal reduction method, as in the preparation of the oxidation catalyst. The above mentioned catalyst is then calcined at high temperatures, for example, 500-600°C, to obtain the catalyzed wall-flow filter.

The support used for the oxidation catalyst is exemplified
15 by flow-through ceramic honeycomb monolith.

Also, the support or filter used for the catalyzed wall-flow filter includes wall-flow ceramic honeycomb filter, ceramic foam, ceramic fiber filter, metal honeycomb, metal foam, metal mesh, etc. In particular, wall-flow ceramic honeycomb filter is
20 preferable.

In the present invention, more easily combustible materials including carbon monoxide, unburned hydrocarbons and soluble organic fraction of particulate matters from the diesel engine exhaust, than the soot particulates, are combusted by the
25 oxidation catalyst prepared from the colloidal solution of the PGM salt and the transition/alkali metal salt. Thereby, the temperature of the exhaust gas arriving at the catalyzed wall-

flow filter downstream increases, thus realizing efficient oxidation of the soot collected on the filter.

Moreover, the oxidation catalyst composition containing the PGM metal salt colloid further has other metal salt colloids of magnesium or cobalt, thereby improving the activity of the PGM. For instance, magnesium oxide acts to increase the activity of the PGM so as to effectively combust the soot particulates collected on the filter.

Use of such an oxidation catalyst leads to efficient conversion of carbon monoxide, unburned hydrocarbons, and volatile organic fractions while inducing a favorable conditions for combustion of the soot particulates on the catalyzed filter downstream.

The combustion of the soot particulates trapped in the catalyzed wall-flow filter is facilitated with the aid of a strong oxidizing agent, such as, nitrogen dioxide, the catalytic components of at least one PGM and alkali metal, etc. supported to the filter, as well as the activated oxygen. Carbon dioxide, a completely oxidized product of the soot particulates, is discharged to the atmosphere.

On the other hand, alkali metal component of the catalyzed wall-flow filter composition, such as potassium, acts to enhance the surface activity of the precious metal catalyst bringing the catalyst into tight-contact with the particulates while improving dispersion and reducibility of the metal catalyst.

Furthermore, with the use of the catalytic filter containing the oxidation catalyst and the catalyzed wall-flow

filter of the present invention, the temperature required to initiate the combustion of the soot particulates collected on the catalyzed wall-flow filter upon diesel engine operation decreases. In addition, BPT (Balance Point Temperature), the
5 temperature at which the rates of soot accumulation and soot combustion are balanced to each other, decreases to 300-320°C, that is a sufficiently low temperature to continuously remove soot particulates at the typical exhaust temperature from diesel engines, and therefore, the catalytic filter of the present
10 invention can be continuously regenerated without an additional active regeneration device.

Engine dynamometer tests were carried out for the catalytic filter mounting the oxidation catalyst and the catalyzed wall-flow filter of the present invention, and the
15 test results showed the reduction of 92% or more of the soot particulates, 85% or more of CO and HC, and ca. 19% of NO_x.

A better understanding of the present invention may be obtained through the following examples which are set forth to illustrate, but are not to be construed as the limit of the
20 present invention.

EXAMPLE 1

(1) Preparation of Colloidal Metal Salt Solution

- Platinic Colloidal Solution

25 In a 2 L flask, 252 g of polyvinylpyrrolidone (average molecular weight: 10,000, Aldrich Chemical) was dissolved in 1 L of deionized water to make a uniform solution, which was then

added with 30.4 g of chloroplatinic acid and 1 L of methanol with vigorous stirring. The solution was refluxed at 80°C for 6 hours, and filtered to obtain 2,070 g of a dark brown platonic colloidal solution containing 0.62 wt% of platinum.

5 - Preparation of Aqueous Metal Salt Solution

15.4 g of ammonium molybdate, 40 g of magnesium nitrate, and 10 g of potassium hydroxide were added to 250 mL of deionized water with vigorous stirring, to prepare aqueous solutions of molybdenum, magnesium, and potassium.

10 - Preparation of Colloidal Solution Mixture

The above platonic colloidal solution was mixed with the aqueous magnesium solution at a weight ratio of 1:1, to make a colloidal metal salt solution for oxidation catalyst. Further, the platonic colloidal solution, the aqueous molybdenum
15 solution, and the aqueous potassium solution were mixed at the same weight ratio, to obtain a colloidal metal salt solution for catalyzed wall-flow filter.

(2) Preparation of Catalytic Filter

A flow-through ceramic monolith having a diameter of 5.66
20 inch, a length of 3 inch and a cell density of 400 cpsi was used as a substrate of the oxidation catalyst and a wall-flow ceramic filter having a diameter of 5.66 inch, a length of 6 inch and a cell density of 100 cpsi was used as a substrate of the catalyzed wall-flow filter. To the ceramic monolith, ca. 30
25 wt% of titania and silica slurry solution was washcoated, followed by drying and calcination. Further, to the wall-flow ceramic filter, 7 wt% of titania and silica slurry solution was

16

washcoated, followed by drying and calcination. The colloidal PGM solutions for oxidation catalyst and catalyzed wall-flow filter were washcoated to the supports, respectively, and then dried at 120°C for 3 hours, and calcined at 500-600°C for 4-6 hours, to prepare the catalytic filters.

EXAMPLE 2

A catalytic wall-flow filter for removal of soot from diesel engine exhaust was prepared in the same manner as in Example 1, with the exception that flow-through ceramic monolith having a diameter of 10.5 inch, a length of 3 inch and a cell density of 400 cpsi, and wall-flow ceramic filter (Corning Inc.) having a diameter of 10.5 inch, a length of 12 inch and a cell density of 200 cpsi, were used as substrates for the oxidation catalyst and the catalyzed wall-flow filter.

EXAMPLE 3

The catalytic filter prepared in Example 2 mounted to an exhaust pipe of Hyundai Aerocity Bus 540 having an exhaust air volume of 11,149 cc, and subjected to field test in D-13 mode. Subsequently, the reduction of soot particulates in exhaust gas was measured. The results are depicted in FIGS. 1a to 1d.

As is shown in FIGS. 1a to 1d, the catalytic filter of the present invention reduced 92% or more of soot particulates (PM), 85% of CO and HC, and 19% of NO_x.

EXAMPLE 4

The catalytic filter of Example 2 was mounted to a diesel engine, and the change of BPT with respect to RPM and torque was measured. The results are given in FIG. 2.

As is shown in FIG. 2, the catalytic filter of the present invention showed a BPT of 300-320°C.

EXAMPLE 5

The catalytic filter of Example 2 was mounted to an urban bus driving in Seoul, Korea, and the backpressure of DPF, which indicates the amount of soot particulates collected in the filter, was monitored daily.

As is illustrated in FIG. 3, it was confirmed that the collected amount of soot particulates in the catalytic filter was maintained at a constant level during the test period. This means that the soot particulates collected on the filter are removed periodically by combustion. Thereby, conventional problems, such as excessively high exhaust gas pressure drop in the filter that would negatively affect the engine operation, can be avoided.

20 Industrial Applicability

As described above, the present invention provides a catalytic filter for removal of soot particulates from diesel engine exhaust and a preparation method thereof. When the catalytic filter of the present invention is applied to diesel vehicles, the soot particulates collected on the filter can be

continuously removed, also abating gaseous pollutants (CO, HC and NO_x) from the diesel engine exhaust.

Although the preferred embodiments of the present invention have been disclosed for illustrative purposes, those
5 skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.

Claims

1. A catalytic filter for removal of soot particulates from diesel engine exhaust, comprising:

an oxidation catalyst positioned upstream of the catalytic
5 filter, prepared by treating a PGM (platinum group metal) salt and a transition/alkali metal salt with a water-soluble polymer compound and a reducing agent, to obtain a first colloidal mixture solution, which is then washcoated to a catalyst-support-coated monolithic ceramic substrate; and

a catalyzed wall-flow filter positioned downstream of the catalytic filter, prepared by treating a PGM (platinum group metal) salt and a metal salt mixture including at least one selected from a first group of catalyst metal to enhance oxidation activity and at least one selected from a second group of catalyst metal to decrease a combustion temperature of soot particulates, with a water-soluble polymer compound and a reducing agent, to obtain a second colloidal mixture solution, which is then washcoated on a catalyst-support-coated wall-flow filter.

10 2. The catalytic filter according to claim 1, wherein the metal salt mixture used for the catalyzed wall-flow filter further comprises at least one selected from a third group of catalyst metal to prevent oxidation of sulfur dioxide.

3. The catalytic filter according to claim 1 or 2, wherein

the catalyst support comprises active alumina, silica, and/or titania.

4. The catalytic filter according to claim 1 or 2, wherein the catalyst support contains 0.1-1.5 g/in³ of TiO₂ and 0.1-1.5 g/in³ of SiO₂, with a weight ratio of TiO₂ to SiO₂ of 2-4:1.

5. The catalytic filter according to claim 1 or 2, wherein the platinum group metal salt comprises Pt, Pd, Ru, Ir, Rh, or combinations thereof.

6. The catalytic filter according to claim 1 or 2, wherein the transition/alkali metal salt comprises Ba, Ce, Co, Cr, Cs, Cu, Fe, K, Mg, Mn, Mo, Ni, Pb, V, W, or combinations thereof, and a weight ratio of the platinum group metal to the transition/alkali metal is in a range of 1:0.1-5.

7. The catalytic filter according to claim 1 or 2, wherein the oxidation catalyst contains 5-45 g/ft³ of platinum group metal.

8. The catalytic filter according to claim 1, wherein the first group of catalyst metal is selected from Ba, Cr, Mn, Fe, Co, Ni, Cu, Mo, V and Pb, and the second group of catalyst metal is selected from Li, Na, K, Mg, Ca and Cs.

9. The catalytic filter according to claim 1 or 8, wherein

the catalyzed wall-flow filter contains 5-45 g/ft³ of the platinum group metal, 10-120 g/ft³ of the first group of catalyst metal, and 5-40 g/ft³ of the second group of catalyst metal.

5 10. The catalytic filter according to claim 2, wherein the first group of catalyst metal is selected from Ba, Cr, Mn, Fe, Co, Ni, Cu, Mo, V and Pb, and the second group of catalyst metal is selected from Li, Na, K, Mg, Ca and Cs, and the third group of catalyst metal is selected from V, W and Mo.

10 11. The catalytic filter according to claim 2 or 10, wherein the catalyzed filter contains 5-45 g/ft³ of the platinum group metal, 10-120 g/ft³ of the first group of catalyst metal, 5-40 g/ft³ of the second group of catalyst metal, and 10-150 g/ft³ of the third group of catalyst metal.

15 12. The catalytic filter according to claim 1 or 2, wherein the catalyst-support-coated monolithic ceramic substrate comprises flow-through ceramic honeycomb monolith, and the catalyst-support-coated wall-flow filter comprises wall-flow ceramic honeycomb filter, ceramic foam, ceramic fiber filter,
20 metal honeycomb, metal foam, or metal mesh.

13. A method of preparing a catalytic filter for removal of soot particulates from diesel engine exhaust, comprising:

treating a PGM (platinum group metal) salt and a

transition/alkali metal salt with a water-soluble polymer compound and a reducing agent, to obtain a first colloidal mixture solution, which is then washcoated to a catalyst-support-coated monolithic ceramic substrate, followed by
5 calcination process at high temperatures, to obtain an oxidation catalyst; and

treating a PGM (platinum group metal) salt and a metal salt mixture including at least one selected from a first group of catalyst metal to increase oxidation activity for nitrogen
10 oxide and at least one selected from a second group of catalyst metal to decrease a combustion temperature of soot particulates, with a water-soluble polymer compound and a reducing agent, to obtain a second colloidal solution, which is then washcoated on a catalyst-support-coated wall-flow filter, followed by
15 calcination process at high temperatures, to obtain a catalyzed wall-flow filter.

14. The method according to claim 13, wherein the metal salt mixture used for the catalyzed wall-flow filter further comprises at least one selected from a third group of catalyst
20 metal to prevent oxidation of sulfur dioxide.

15. The method according to claim 13 or 14, wherein the water-soluble polymer compound comprises polyvinylalcohol, polyvinylpyrrolidone, or polymethylacrylate.

16. The method according to claim 13 or 14, wherein the

reducing agent comprises methanol, ethanol, hydrazine, or a mixture of methanol/sodium hydroxide.

17. The method according to claim 13 or 14, wherein the catalyst-support comprises active alumina, silica and/or titania.

18. The method according to claim 13 or 14, wherein the platinum group metal salt comprises Pt, Pd, Ru, Ir, Rh, or combinations thereof.

19. The method according to claim 13 or 14, wherein the transition/alkali metal salt comprises Ba, Ce, Co, Cr, Cs, Cu, Fe, K, Mg, Mn, Mo, Ni, Pb, V, W, or combinations thereof, and a weight ratio of the PGM to the transition/alkali metal is in a range of 1:0.1-5.

20. The method according to claim 13, wherein the first group of catalyst metal is selected from Ba, Cr, Mn, Fe, Co, Ni, Cu, Mo, V and Pb, and the second group of catalyst metal is selected from Li, Na, K, Mg, Ca and Cs.

21. The method according to claim 14, wherein the first group of catalyst metal is selected from among Ba, Cr, Mn, Fe, Co, Ni, Cu, Mo, V and Pb, and the second group of catalyst metal is selected from among Li, Na, K, Mg, Ca and Cs, and the third group of catalyst metal is selected from among V, W and Mo.

1/4




FIG. 1a




FIG. 1b

2/4




FIG. 1c




FIG. 1d

3/4




FIG. 2

4/4




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR2004/000856**A. CLASSIFICATION OF SUBJECT MATTER****IPC7 B01D 39/00**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7 B01D 39/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

KIPASS, USP, PAJ "FILTER, DIESEL, MATAL, CATALYST, OXIDE"

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 369163 A1 (SAKAI CHEMICAL INDUSTRY CO., LTD.) 23 May 1990 See the whole document	1-21
A	US 4,973,435 A (ALCAN INTERNATIONAL LIMITED) 27 November 1990 See the abstract and column2 line11 - column6 line46	1-21
A	JP 9-52908 A (IDEMITSUKOSAN CO., LTD.) 25 February 1997 See the abstract and claims1-6	1-21
A	JP 2002-119809 A (TOYOTA CENTRAL RES & DEV LAB INC.) 23 April 2002 See the whole document	1-21
A	JP 1-199613 A (CATALERKOGYO KK) 11 August 1989 See the whole document	1-21

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

30 JULY 2004 (30.07.2004)

Date of mailing of the international search report

31 JULY 2004 (31.07.2004)

Name and mailing address of the ISA/KR

Korean Intellectual Property Office
920 Dunsan-dong, Seo-gu, Daejeon 302-701,
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

JWA, Seung Kwan

Telephone No. 82-42-481-5560



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR2004/000856

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 369163 A1	23.05.1990	US 5,162,287 A JP 2-102315 A2	10.11.1992 13.04.1990
US 4,973,435 A	27.11.1990	NONE	
JP 9-52908 A	25.02.1997	NONE	
JP 2002-119809 A	23.04.2002	NONE	
JP 1-199613 A	11.08.1989	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.